

# **GenLight 2X Commercial Solar Sign Light**


GenLight-12v-2X-V1

<b>Light Fixture Specifications</b>	
Model	GenLight-12v-2X-V1
# of LEDs	120
Light Output	1000 Lm
Light Output (equivalent)	150 - 250W
Max Sign Illumination Area	10' x 14'
Max Area Illumination	35' x 35' @ 20'
Lighting Circuit Efficiency	85%
Dimensions	11" x 9" x 3.5"
Weight	13.8 lbs
Operating Run Time (max)	8 - 12 hrs
Operating Modes	Auto / Off / Charge

Solar Panel & Battery Specifications	
Solar Panel Type	Monocrystalline
Solar Panel Voltage	18V
Solar Panel Wattage	10W
Solar Panel Dimensions	13.2" x 11" x 0.7"
Solar Panel Weight	5 lbs
Battery Type	Li-lon
Battery Voltage	12V
Battery Capacity	8 ahr

Accessories & Replacement Components	
Replacement Battery	Batt-GenLight120LED-Replacement
Top / Bottom Mounting Arm (for light fixture)	GenLight-TP-4FT-EXT
Side Pole Mounting Arm (for solar panel)	PowerMount-SP-SA13

## **Components & Technical Description**



## 1. 120 Ultra Bright LEDs

Our high-intensity white LEDs deliver dazzling light and beautiful wide-angle coverage of your sign at night

### 2. WEATHERPROOF ALUMINUM BODY

Rugged enough to stand up to the toughest climates including cold, northern winters, the GenLight 2X lasts for years

#### 3. MANUAL ON/OFF SWITCH

Save your battery when you're storing your light – turning off the power manually can significantly increase battery life

#### 4. LIGHT FIXTURE MOUNTING BRACKET

Quickly and securely mount the light fixture to a post or wall with the adjustable, heavy-duty mounting bracket

### **5. HIGH-EFFICIENCY SOLAR PANEL**

The included mono-crystalline solar panel delivers highefficiency, reliable and power and rugged performance

## **6. SOLAR PANEL MOUNTING FRAME**

Tilt mount the solar panel on a roof or the ground with the included, heavy-duty mounting frame in only a few moments

> Innovative Solar Solutions 2917 State Hwy 7 Bainbridge, MY 13733 P: 1.800.786.0329 www.SiliconSolar.com